



Name	Divus Superio MS15	Divus Superio MS15	
<b>Display / resolution</b>	15,6" TFT-LCD / 1366 x 768 / opt. 1920 x 1080	15,6" TFT-LCD / 1366 x 768 / opt. 1920 x 1080	
<b>Viewable Size</b>	344,23mm x 193,54mm	344,23mm x 193,54mm	
<b>Brightness</b>	300 cd m <sup>2</sup>	300 cd m <sup>2</sup>	
<b>Frontplate</b>	Measures: 472mm x 277mm	Measures : 472mm x 277mm	
<b>OSD-keyboard</b>	Backside	/	
<b>Touchsensor /</b>	Projectiv Kapazitiv (Multiouch)	Projectiv Kapazitiv ( Multiouch )	
<b>CPU / RAM</b>	/	Intel 4x2GHz J1900 / 4GB DDR3	Intel i5 7200U / 8GB DDR3
<b>HDD</b>	/	64GB SSD	128GB SSD
<b>Front Connections</b>	USB	1 x USB / Power Taster	
<b>Back Connections</b>	DVI-I, Displayport	2x USB 2.0, 2x Ethernet, VGA, RS232, HDMI	2xUSB2.0,4xUSB3.0,1xHDMI, 1xDisplayport,2xEthernet
<b>OS</b>	/	Windows 10 Pro/Linux	
<b>Cooling</b>	Passive	Passive	
<b>Speaker</b>	Yes	Yes	
<b>Microphone</b>	Yes	Yes	
<b>Options</b>	Case anodized brushing	Case anodized brushing	
<b>Power Supply</b>	110 - 240 VAC / 12VDC	110 - 240 VAC / 12VDC	
<b>Power Consumption Load / Standby</b>	15 W / 0.5 W	26 W / 5 W	34 W / 5W
<b>Operating temperature</b>	0°C to +40°C	0°C to +40°C	
<b>Storage temperature</b>	-20°C to+ 60°C	-20°C to +60°C	
<b>Storage humidity</b>	Max. 80% (not condensated)	Max. 80% (not condensated)	
<b>Weight</b>	4,5kg	4,5kg	
<b>Accessoires</b>	Incl. Adaptercase and mount utility		
<b>RoHs compliant</b>	yes	yes	
<b>Standards</b>	CE Konform / VDE 0700/0701 EN 55024:1998 + A1:2001 + A2:2003 Teile: EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, IEC 61000-4-6, EN 61000-4-11		